




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 9/46		(11) International Publication Number: WO 96/37834
A1		(43) International Publication Date: 28 November 1996 (28.11.96)
(21) International Application Number: PCT/US96/07843 (22) International Filing Date: 24 May 1996 (24.05.96) (30) Priority Data: 08/450,251 25 May 1995 (25.05.95) US (71) Applicant: CRAY RESEARCH, INC. [US/US]; 655-A Lone Oak Drive, Eagan, MN 55121 (US). (72) Inventors: KESSLER, Richard, E. ; 3732 Oakhill Place, Eau Claire, WI 54703 (US). OBERLIN, Steven, M. ; 20 Peterson Lane, Chippewa Falls, WI 54729 (US). THORSON, Gregory, M. ; 1119 Sweet Water Close, Altoona, WI 54720 (US). (74) Agent: VIKSINNS, Ann, S. ; Schwegman, Lundberg, Woessner & Kluth, P.O. Box 2938, Minneapolis, MN 55402 (US).		(81) Designated States: European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: BARRIER AND EUREKA SYNCHRONIZATION ARCHITECTURE FOR MULTIPROCESSORS

(57) Abstract

Method and apparatus for facilitating barrier and eureka synchronization in a massively parallel processing system. The present barrier/eureka mechanism provides a partitionable, low-latency, immediately reusable, robust mechanism which can operate on a physical data-communications network and can be used to alert all processor entities (PEs) in a partition when all of the PEs in that partition have reached a designated barrier point in their individual program code, or when any one of the PEs in that partition has reached a designated eureka point in its individual program code, or when either the barrier or eureka requirements have been satisfied, whichever comes first. Multiple overlapping barrier/eureka synchronization partitions are available simultaneously through the use of a plurality of parallel barrier/eureka synchronization domains. The present barrier/eureka mechanism may be implemented on either a dedicated barrier network, or superimposed as a virtual barrier/eureka network operating on a physical data-communications network which is also used for data interchange, operating system functions, and other purposes.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

Barrier and Eureka Synchronization Architecture for Multiprocessors

5

Field of the Invention

The present invention relates to methods and apparatus for multiprocessor systems and more specifically to synchronization of processes running on multiprocessor systems.

10

Background of the Invention

Massively parallel processing (MPP) systems are computing systems comprised of hundreds or thousands of processing elements (PEs). While the power of a multiple-instruction multiple-data (MIMD) MPP computer system lies in its ability to execute independent threads of code simultaneously, 15 the inherently asynchronous states of the PEs (with respect to each other) makes it difficult in such a system to enforce a deterministic order of events when necessary. Program sequences involving interaction between multiple PEs such as coordinated communication, sequential access to shared resources, controlled transitions between parallel regions, etc., may require synchronization of the PEs 20 in order to assure proper execution.

Very fast synchronization is required for high-performance highly parallel processing with asynchronous processors (i.e., processors which execute programs independently of each other). This synchronization involves communication among the computational entities which work together on an 25 overall application program. An important synchronization capability in any programming model is the "barrier". Barriers are points placed in the code beyond which no processor participating in a particular computation is to be allowed to proceed until all processors have arrived at their respective barrier points. Since PEs may wait at a barrier until alerted that all PEs have arrived at 30 the barrier, it is very important to minimize the latency of the barrier mechanism. The latency of a barrier mechanism is defined as the period of time between when the last processor arrives at a barrier, and when all processors have been notified that the requirements of the barrier have been satisfied (the term for meeting these requirements is also called "satisfying the barrier"). During this

period of time, all PEs may be idle waiting for the barrier to be satisfied. Hence barriers can be used as a serialization point in a parallel code (a point from which all PEs can proceed ahead, having waited for other PEs to be synchronized).

Because a barrier defines a serialization point in a program, it is important to

- 5 keep the barrier latency as low as possible, in order that the work to be done after the barrier can be started as soon as possible.

Another important synchronization capability in any programming model is the "eureka". Eureka are points placed in the code which notify all other processors of a particular group of processors participating in a

- 10 computation that one processor has reached that eureka point in its computation.

Typically, the eureka point is a notification that the processor has reached a solution to the computation (e.g., found the item being searched for by the group). Since processors will typically abandon the work they are doing upon being notified that another PE has arrived at its eureka point, it is also very

- 15 important to minimize the latency of the eureka mechanism. The latency of a eureka mechanism is defined as the period of time between when the first processor arrives at a eureka, and when all processors have been notified that the eureka has been satisfied. During this period of time, all other PEs may be doing fruitless computation even though the eureka has been satisfied. As soon as the
20 other PEs have been notified that the eureka has been satisfied, they can proceed to the next stage of their computation. Hence eureka can also be used as a serialization point in a parallel code. Because a eureka defines a serialization point in a program, it is important to keep the eureka latency as low as possible.

- Barriers and eureka can be implemented entirely by software
25 means, but software schemes are typically encumbered by long latencies and/or limited parallelism restricting how many processors can arrive at the barrier simultaneously without artificial serialization (e.g., atomic test-and-set or read-modify-write type operations which impose serialization by software convention or style).

- 30 Hardware support for barriers and eureka, while reducing the latency problems associated with barriers and eureka implemented by purely

software means, can have other shortcomings that limit the utility of the mechanism in a production computing system. (Production computing systems, which support many users and often have less controlled environments than do more theoretical test-bed computing systems, demand that the barrier resource and eureka resource -- like all resources -- be partitionable among multiple users while maintaining protective boundaries between users.) In addition, the barrier resource and eureka resource must have functions which are rich enough to allow isolation between the operating system and the user executing within the same partition. Provision must also be made for fault tolerance to insure the robust nature of the barrier and eureka mechanism.

Hardware mechanisms may also suffer from an inability to operate synchronously. This inability may require that a PE, upon discovering that a barrier has been satisfied (all PEs have arrived at that barrier point in the program) or that a eureka has been satisfied (one PE has arrived at that eureka point in the program), wait until all PEs have discovered that the barrier or eureka has been reached before it may proceed through the next section of program code. The ability to operate synchronously enables the barrier mechanism and eureka mechanism to be immediately reusable without fear of race conditions (e.g., where, due to timing variances, some PEs cannot determine whether the barrier is being "armed" (initialized), has been armed, or has been satisfied).

Hardware mechanisms may also require that a PE explicitly test a barrier flag or eureka flag to discover when the respective condition has been satisfied. This can prevent a PE from accomplishing other useful work while the barrier remains unsatisfied, or force the programmer to include periodic tests of the barrier and eureka into the program in order to accomplish other useful work while a barrier or eureka is pending. This can limit the usefulness of a eureka mechanism when used as a means of terminating speculative parallel work (e.g., a database search) when the work has been completed (e.g. the searched-for item has been found).

Hardware mechanisms may require that the overall barrier tree be hardwired in a rigid configuration. While sub-portions of the barrier tree may be used for separate barrier networks, there is often little flexibility to configure various barrier trees.

5 It is often desirable to allocate some, but not all, of the processors in a parallel processing network to some particular application (software) program, and to use the other remaining processors for some other program. This allocation can change over time. It is thus desirable to have a subset of all processors in a parallel-processing network participating in a barrier and/or
10 eureka synchronization, and to be able to dynamically change the configuration over time.

Summary of the Invention

The present invention provides a method and apparatus that facilitates highly functional barrier and eureka synchronization in a massively
15 parallel processing system. The present barrier/eureka mechanism provides a partitionable, low-latency, immediately reusable, robust mechanism which can operate on a physical data-communications network and can be used to alert all PEs in a partition when all of the PEs in that partition have reached a designated barrier point in their individual program code, or when any one of the PEs in that
20 partition has reached a designated eureka point in its individual program code, or when either the barrier or eureka requirements have been satisfied, whichever comes first. Multiple overlapping barrier/eureka synchronization partitions are available simultaneously. The present barrier/eureka mechanism may be implemented on either a dedicated barrier network, or superimposed as a virtual
25 barrier/eureka network operating on a data-communications network which is also used for conventional data interchange, operating system functions, and other purposes.

The present invention also teaches a method and apparatus for a node router for use in a multiprocessor computer system. The node router
30 includes a plurality of node interconnection ports operable to connect the node router to a plurality of other node routers, a BES state register, and a BES

messaging circuit coupled to the node interconnection ports. The BES messaging circuit selectively sends and receives BES messages between the node router and the other node routers. The BES messages include a barrier-join message, a eureka message, and a barrier-complete message. In one
5 embodiment, counts of outstanding memory operations are maintained at each node, and before a barrier (or eureka) is joined, the hardware checks to make sure there are no outstanding memory operations. The node router also includes a BES-state changer coupled to the BES-state register and to the BES-messaging circuit. The BES-state changer changes the contents of the BES-state register
10 responsive to a BES state stored in the BES-state register and to a BES message received by the BES-messaging circuit.

According to another aspect of the present invention, the node router also includes a barrier/eureka synchronization (BES) child-connection register coupled to the node-interconnection ports, wherein the BES child-
15 connection register specifies which of the other node routers are children of this node router. The node router also includes a BES parent-connection register coupled to the node-interconnection ports, wherein the BES parent-connection register specifies which one of the other node routers is a parent of this node router.

20 According to another aspect of the present invention, a method is provided to perform the BES function.

Brief Description of the Drawings

In the following detailed description of the invention, reference is made to the accompanying drawings which form a part hereof, and in which is
25 shown by way of illustration only, specific exemplary embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized, and structural changes may be made, without departing from the scope of the present invention.

FIG. 1 is a simplified block diagram illustrating an exemplary multiprocessor
30 system 100 on which the barrier-eureka synchronization (BES) architecture of the present invention can be used.

FIG. 2 is a simplified block diagram illustrating an embodiment of a physical node 200 comprised of a node router 140 and processing element (PE) 102 including processor 202, interface-and-network router 206, and local memory 204.

5 FIG. 3 is a schematic diagram illustrating the software flow at a barrier synchronization point 106.

FIG. 4 is a flow diagram of the software running in one PE 102 which uses both barrier and eureka synchronization.

FIG. 5 is a topology diagram of a hardwired barrier-synchronization circuit for barrier synchronization, which can also be used for eureka
10 synchronization using negative logic.

FIG. 6 is a topology diagram of an exemplary configured BES entity 80.

FIG. 7 is a topology diagram of two exemplary BES entities 80.1 and 80.2 as configured in an exemplary 2-D BES domain 82.

15 FIG. 8 is a topology diagram of three exemplary BES entities 80.1, 80.2, and 80.3 as configured in two exemplary 2-D BES domains 82.1 and 82.2 which are running on an exemplary 2-D multiprocessor system 100.

FIG. 9 is a block diagram of an exemplary multiprocessor system 100 including both memory and data-communication function 132 and BES
20 communication function 130.

FIG. 10 is a block diagram of an embodiment of a physical node of multiprocessor system 100 showing generalized blocks of the BES state information.

FIG. 11 is a block diagram of an embodiment of a node of multiprocessor
25 system 100 showing blocks of the BES state information for a 3-D torus.

FIG. 12 is a block diagram showing an embodiment of connection state information.

FIGs. 13A and 13B are block diagrams of an embodiment of a node showing
30 the separation and merger of BES messages from and with normal data messages, respectively.

- FIG. 14 is a table of FANIN state transitions.
- FIG. 15 is a table of FANOUT state transitions.
- FIG. 16 is a state transition diagram of simple eureka transitions.
- FIG. 17 is a state transition diagram of simple barrier transitions.
- 5 FIG. 18 is a table of BES unit states.
- FIG. 19 is a table of BES unit operations.
- FIG. 20 shows the placement of FIGs. 20A and 20B side-by-side to form a single table.
- FIGs. 20A and 20B, placed next to one another as shown in FIG. 20, form a
- 10 table of BES-unit state transitions.
- FIG. 21 is an exemplary structure of a barrier register address 210.
- FIG. 22 shows a conceptual diagram of the barrier/eureka-synchronization connections of a portion of a three-dimensional torus network of physical nodes 200.
- 15 FIG. 23 is a table showing an example configuration for a BES entity 80 operating on the network portion shown in Figure 22.
- FIG. 24 is a table showing an example encoding for parent node values which are used in one embodiment of PTRCI register 722.

Description of the Preferred Embodiment

- 20 In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings which form a part hereof, and in which are shown by way of illustration specific embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized and structural changes may be made without
- 25 departing from the scope of the present invention.

The barrier/eureka synchronization (BES) architecture of the present invention provides an inexpensive means to support both barrier- and eureka-synchronization operations with any existing (or added) inter-processor data-communication network. The preferred network is asynchronous (i.e.,

30 "asynchronous" here means a network which operates to transmit data independently of the processing occurring within the attached PEs), and

preferably uses point-to-point communication channels. (Point-to-point communications channels link one point to one other point, as opposed to one-to-many channels such as busses or broadcast systems.) The routing nodes of the normal MPP communication network cooperate, communicating via special
5 messages along the existing (or added) direct connections in order to provide very fast, parallel resolution of the synchronization operations. Since only the already-available inter-processor communication network and routing nodes, rather than an additional network, are preferably used to implement the synchronization primitives (those basic operations used as building blocks for
10 higher-level functions), the system can be implemented at little or no additional cost to the network, while still providing high-flexibility, low-latency synchronization.

Figure 1 is a simplified block diagram illustrating an exemplary multiprocessor system 100 on which the present barrier-eureka synchronization
15 (BES) architecture can be used. Multiprocessor system 100 is comprised of a plurality of physical nodes 200. Each physical nodes 200 is comprised of at least one processor 202, local memory 204, and an interface which can be thought of as a portion of the interconnection network. In one exemplary embodiment, local memory 204 is globally addressable by each processor 202, but physically
20 distributed among physical nodes 200, with between 64 megabytes and 512 megabytes per node, and the number of physical nodes 200 is up to approximately 2048 nodes. In one such exemplary embodiment, spare nodes and "pass-through" nodes are added to multiprocessor system 100 as well. Multiprocessor system 100 is also comprised of a plurality of input/output (I/O)
25 devices 300 such as high-performance disk-drive subsystems, tape subsystems, communications subsystems, and/or user terminals, connected to input/output (I/O) channels capable of transfer rates up to 500 megabytes per second.

Figure 2 is a simplified block diagram illustrating an embodiment
of a physical node 200 comprised of a node router 140 and processing element
30 (PE) 102, the PE 102 which includes processor 202, interface-and-network

router 206, and local memory 204. In this embodiment shown in Figure 2, interface-and-network router 206 includes node router 140.

In general, a "processing element" (also called a "processing entity") (PE) 102 is defined as a computational entity which executes a PE
5 program. The PE program is generally part of a larger program (also called the "application") which executes an software program applied to a specific use for a user. PEs 102 can be, but need not be, separate pieces of hardware (e.g., individual nodes 200 of an MPP system 100), and can also be implemented as a plurality of processes, threads, tasks, or other program elements which run on a
10 single hardware processor or on a plurality of hardware processors connected by a network. A plurality of PEs 102 can share a single piece of hardware, such as processor 202 and memory 204, in a time-slice manner. In another embodiment, a plurality of processors 202 can simultaneously execute as a single PE 102 in a vector-processing manner. Thus, a PE 102 and a processor 202 can be but need
15 not be co-extensive.

A "BES entity" (sometimes also called a "synchronization tree") is defined as the set of PEs 102 which are grouped together, preferably by software configuration operations, to synchronize on a particular barrier or eureka event or a hybrid set of barrier/eureka synchronization events.

20 Figure 3 is a schematic diagram illustrating the software flow at a barrier synchronization point. In general, several job instantiations 103 operate simultaneously within multiprocessor system 100. This simultaneity can mean a method of operation where job instantiations 103 operate in separate PEs 102 which operate at the same time, or it can mean that certain job instantiations 103
25 operate in a time-multiplexed manner within a single PE 102, or it can mean a combination of these previous two methods. Within each job instantiation 103, there is antecedent work 104 which is performed until some condition is detected in the program code which causes the signalling of a barrier point 106. Barrier point 106 causes that job instantiation 103 to wait at barrier 110 until all other
30 job instantiations 103 reach their respective barrier point 106, and thus join barrier 110.

As soon as the particular job instantiation 103 running on a particular PE 102 joins the barrier 110, that PE 102 is then available to start work on another job instantiation 103. For example, suppose a computational task can be divided into eight parts and further that four PEs 102 are available to work on this task. Four job instantiations 103 could then begin on the antecedent work 104 of four of the eight parts of the task. As each processor reached its individual barrier point 106, it would join barrier 110, swap out the current job instantiation 103 (which can proceed no further until all eight job instantiations 103 join barrier 110), and swap in a new job instantiation 103 to process the next of the eight parts. Once all eight job instantiations 103 reached barrier 110, the four PEs 102 can continue to finish the subsequent work 108 of four job instantiations 103. Such a scheme can provide more efficient utilization of computational resources than were eight PEs 102 to be used, in which case seven PEs 102 could be waiting idle at barrier 110 until the last PE 102 finally reached its own barrier point 106 and joined barrier 110. On the other hand, maximum performance can often be achieved by using as many parallel-operating PEs 102 on a problem as possible. For simplicity, this patent disclosure will equate a job instantiation 103 with the PE 102 on which it is running, unless it is clear from the context that the two are distinct.

Figure 4 is a flow diagram of exemplary software running in one PE 102 which uses both barrier and eureka synchronization. At block 120, computational work is done; for example, searching for an item in a portion of a database. Periodically, at block 122, a test is performed to determine whether the item being sought has been found, and if so, a control is passed to block 124 and a "eureka" is sent to all other PEs 102 which are also searching for the same (or another corresponding) item in other portions of the database; then control is passed to block 129, and this PE 102 joins the barrier 110. If, at block 122, the item has not been found by this PE 102, then control passes to block 126, where a test is made to determine whether any other PE 102 has sent a eureka which that PE 102 found its item, and if so, control is passed to block 129, and this PE 102 joins the barrier 110. If, at block 126, no other PE 102 has sent a eureka,

control is passed to block 128, and a test is made to determine whether this PE 102 has finished searching its portion of the database; and if so, control is passed to block 129, and this PE 102 joins the barrier 110. If, at block 129, this PE 102 has not finished searching its portion of the database, control is passed back to
5 block 120, and work continues as above.

Figure 5 is a topology diagram of an exemplary hardwired barrier synchronization circuit (which can also be used for eureka synchronization using negative logic). Such a circuit is described in copending and commonly assigned application serial number 08/165,265. Communications network 32 is
10 used for normal memory and data communications traffic between the plurality of processors 102. In one exemplary network, one thousand twenty-four (1024) PEs 102 are connected in a three-dimensional torus network. The PEs 102 also communicate through a separate physical barrier/eureka network 30 which has hardwired fanin circuits 33 and fanout connections 34. At any level, (e.g., one of
15 levels 1 through 5) the output of the fanin circuit 33 can be connected to the corresponding fanout connection 34, allowing a limited customization of the tree. In the example shown, the fanin circuit 34 is connected to the fanout 34 at level 5, thus connecting all 1024 PEs 102 into a single barrier.

Figure 6 shows the connection topology for an exemplary
20 embodiment of a BES entity 80. BES entity 80 has a plurality of leaves 74, a single root 70, and a set of branches 72 connecting leaves 74 to root 70 through intermediate internal nodes 76. In one embodiment, referring to Figure 2, each leaf 74 can be thought of as operating within a PE 102, branches 72 can be thought of as being programmable connections operating in node router 140 to
25 other node routers 140. "Barrier events" and/or "eureka events" travel ("FANIN") from the leaves 74 to the root 70, and then travel ("FANOUT") back to the leaves 74. The FANOUT path preferably traces back the same paths (but in the opposite direction) that the FANIN paths took towards the root (but the FANOUT path need not go back along the same paths, nor go back to the same
30 leaves).

Referring to Figure 7, a BES domain 82 (also called a "BES context", but the term "BES domain" is preferred for this description of the invention in order to avoid confusion with "program contexts" used to designate aspects of the multitasking program environment which are saved and restored as part of task switching) is a mechanism within which one or more BES entities 80 can be implemented simultaneously. In one embodiment, each such BES entity 80 operating within a single BES domain 82 is non-overlapping (relative to other BES entities 80 within that same BES domain 82), and has its own root 70, branches 72 and leaves 74, none of which are shared by another BES entity 80 operating within that same BES domain 82. Figure 7 shows a schematic representation of one such exemplary embodiment of a BES domain 82 having two BES entities 80.1 and 80.2 as implemented on a five-by-five two-dimensional (2-D) array of PEs 102. BES entity 80.1 in Figure 7 is similar to the single BES entity 80 of Figure 6; however, as shown in Figure 7, up to N non-overlapping BES entities 80.1 through 80.N can simultaneously co-exist (though only 80.1 and 80.2 are shown in exemplary Figure 7), operating within a single BES domain 82. Each square represents a node 76 and the BES domain of one PE 102 which is connected (in this simplified exemplary embodiment) to four adjacent PEs 102, one on each side of the square. In an alternative preferred embodiment, a three-dimensional (3-D) array of PEs 102 is used and connected as a 3-D torus for multiprocessor system 100, wherein each PE 102 is coupled bi-directionally to each of six adjacent PEs 102, represented as one connection on each face of a cube. In one such embodiment, up to 2048 PEs 102 can be connected in a $32 \times 8 \times 8$ processor 3-D torus network (plus spare processors, and one I/O port, capable of transfer rates up to 500 megabytes per second, for every four processors, wherein any processor can use any I/O port), with each PE 102 having a high-performance RISC processor, such as the EV5 ALPHA processor by DEC, for processor 202.

In one simple exemplary embodiment, shown schematically in Figure 8, parallel-processing multiprocessor system 100 supports a plurality of overlapping and co-existing BES domains 82.1 through 82.N. BES domain 82.1

in Figure 8 is similar to the single BES domain 82 of Figure 7; however, as shown in exemplary Figure 8, up to N overlapping BES domains 82.1 through 82.N can simultaneously co-exist, operating within a single system 100. The example parallel multiprocessing system 100 in Figure 8 is connected as a 2-D toroid array of PEs 102. While BES entities 80 within a single BES domain 82 do not overlap (e.g., BES entity 80.1 does not overlap BES entity 80.2), BES entities 80 in separate BES domains 82 are independent, and are allowed to overlap BES entities 80 in other separate BES domains 82 operating in parallel (e.g., BES entity 80.3 does overlap both BES entities 80.1 and 80.2, but is in a separate BES domain 82.2). In an alternative preferred embodiment, a three-dimensional (3-D) array of PEs 102 is used and connected as a 3-D torus for multiprocessor system 100, wherein each PE 102 is coupled bi-directionally to each of six adjacent PEs 102, conceptually represented as one connection on each face of a cube. In one such embodiment, up to 2048 PEs 102 can be connected in a 3-D torus network, with each PE 102 having a high-performance RISC processor, such as the ALPHA processor by DEC, for processor 202.

Two key forms of synchronization between PEs 102 are barrier synchronization and eureka synchronization.

The BES architecture of the present invention provides the user a BES interface with a full suite of operations. These operations allow each BES entity 80 to be used as barrier or eureka, or both barrier and eureka simultaneously. Barriers and eureka may both be simultaneously in flight on the same BES entity 80. Barriers are immediately reusable after completion of the barrier. Eureka are immediately reusable after completion of a barrier (on the same BES entity) indicating that the eureka has been received by all participating PEs 102. Processor interrupts may optionally be generated upon receipt of eureka or barrier completion events. PEs 102 may also poll to determine whether a eureka or barrier completion has occurred.

Using special-purpose BES configuration registers, the interface-and-network routers 206 of the data-communication network are configured to implement FANIN and FANOUT trees of BES entities 80, and interpret/deliver

special messages driving the FANIN and FANOUT trees. Only communication between directly-connected network nodes is required because configuration information is stored and maintained at each node along the path from the leaves 74 to the root 70 (FANIN) and from the root 70 to the leaves 74 (FANOUT).

- 5 The leaves 74 of the BES entities 80 (comprised of PEs 102) are the participants in the synchronization activity; they provide the user-view of the BES entity 80. In one embodiment, the internal nodes 76 of the BES entity 80 are implemented using interface-and-network routers 206 that transparently implement the user-view of the BES entity 80. (I.e., once initialized, interface-and-network routers
- 10 206 operate without the need for further intervention from processor 202, and are thus "transparent" to programs running in processor 202.) The BES entity 80 can have leaves 74 at varying heights (a "leaf height" is the number of nodes between the root 70 and the leaf 74), and the FANIN and FANOUT trees need not be symmetrical in any way, nor do they require any particular network
- 15 topology; the only network restriction in the preferred embodiment is that there exist a communication path from each PE 102 to all other PEs 102 which are part of the particular BES entity 80. Since the BES architecture of the present invention requires very little storage, all the required state and configuration information to implement the FANIN and FANOUT trees can be contained
- 20 directly within the interface-and-network routers 206 of the communication network (thus not taking processor storage), and the barrier messages that flow through the communication medium need not share the buffering needed for the normal data-message traffic. Hence, the messages that implement the barrier/eureka FANIN and FANOUT trees can travel independently of the
- 25 normal messages that traverse the communication medium; their only interaction is that they share the physical communication medium. In one embodiment, one message is passed on every communications link in the network on every clock cycle. In one such embodiment, BES messages are given high priority and data communications are given moderate priority. In one such embodiment, run-time
- 30 network diagnostic messages (used to monitor network integrity when the network is not otherwise being used) are given low priority. If no

communications functions are occurring at a particular clock cycle on a particular communications link, then blank "placeholder" messages are passed on that link.

A typical barrier operation flows toward the root 70 of the BES entity 80 as PEs 102 join the barrier, and reaches the root once all PEs 102 which are members of that BES entity at that time have joined; then the barrier-completion notification is fanned out along the fanout tree toward the leaves. A typical eureka operation flows immediately to the root and is then immediately fanned out to the leaves. Each interface-and-network router 206 node needs only to maintain a few bits of state information, and some configuration bits to define the connection topology of the BES entity 80 (one bit of configuration information for each "child" of the node and a few bits to determine the parent of the node).

Due to the flexibility of the configurations, any subset of the PEs 102 on communications network 32 can be selected to participate in the barrier and/or eureka of BES entity 80. Multiple BES domains 82 allow for multiple overlapping active BES entities 80. Individual BES domains 82 allow any subset of connected PEs 102 to participate in a particular configured BES entity 80. In addition, each BES domain 82 can implement BES entities 80 ("trees") for multiple groups of PEs 102, provided the trees for the different PE groups do not overlap.

Some of the specific solutions the invention provides are:

- very fast barrier/eureka implementation;
- low-cost dual use of communications network 32 to serve both barrier and normal message traffic;
- flexible barrier/eureka functionality;
- multiple BES domains 82;
- flexible partitioning of BES domain 82 into BES entities 80; and
- simultaneous barrier/eureka usage in each BES entity 80.

Figure 3 shows the flow of a typical application program using barrier synchronization. Barrier 110 is a common synchronization point for a

group of PEs 102. A barrier point subroutine or instruction used to implement the barrier 110 is inserted into each PE program running in each respective PE 102 which is a member of the BES entity 80. The programmer writing the application knows that once the barrier 110 completes, all antecedent work 104
5 will have been completed on all participating PEs 102 up to their individual barrier points 106, and no subsequent work 108 will have started on any PE 102 which is participating in (or a member of) that BES entity 80. Thus, after completion of the barrier 110, the application continues and the programmer can infer some behavioral properties. Typically, a barrier 110 has two phases. The
10 first phase involves joining the barrier 110. The second phase involves waiting for the barrier 110 to complete by all other PEs 102 in the BES entity 80 joining the barrier 110.

One usage of eureka synchronization is for a parallel search.

Figure 4 shows one embodiment of the control flow for one PE 102 in a parallel-
15 search application. The main loop has each of the PEs 102 performing work (antecedent work 104) at block 120 (which in this case is searching for an item), each PE 102 checking to determine whether that PE 102 found the item being searched for at block 122, whether any of the other processors found the item at block 126, or if that PE 102 has finished at block 128. After each PE 102 has
20 finished performing its own work (e.g., has exhausted the list of items it was searching), that PE 102 joins a barrier at block 129 with all other finished processors. As soon as one of the processors finds the item searched for, it sends a eureka at block 124 to the other processors. All processors quickly receive the eureka (either at the test at block 126, or perhaps as the result of an interrupt to a
25 PE 102 at the barrier), and the search can be quickly terminated. Note that the protocol works still correctly with any number of processors reaching block 124 substantially simultaneously and each sending eureka.

Figure 9 shows a conceptual view of the system topology. PEs 102 communicate either by barrier/eureka synchronization communication
30 function 130, or by whatever other communication paths exist in memory and data-communication function 132. A plurality of parallel BES communications

functions 130 may be implemented to meet the needs of users of the multiprocessor system 100. (The other communication paths in memory/data-communication function 132 may have other communication/synchronization forms.) In one exemplary embodiment of the present invention, both of these
5 functions are implemented within communication network 32.

The present invention has several advantages over other systems. First, other systems (e.g., the system shown in Figure 5 and used in the Cray T3D MPP system manufactured by Cray Research Inc., the assignee of the present invention) have physically separate networks (e.g., a communications
10 network 32 is separate and independent of a physical barrier/eureka network 30, both as shown in Figure 5) for the two types of communication functions (i.e. memory and data-communications function 132, and BES communications function 130, respectively) shown in Figure 9. This adds costs to those systems for extra input/output pins and wiring. The present invention allows the
15 barrier/eureka synchronization communication function 130 to communicate via the (possibly asynchronous) communication network 32, resulting in a more efficient and cost-effective design. The implementation can be readily adapted to any arbitrary communication topology that allows FANIN and FANOUT trees to be created with the physical or virtual links. Since there is very little required
20 state information, it is possible to hold the full state information of the trees on the individual interface-and-network router 206 at each of the nodes that implement communication network 32. In one embodiment, each of the nodes that implement communication network 32 includes special-purpose registers and control logic in order. The second advancement from other barrier systems is
25 the flexibility-of-use. Each barrier/eureka synchronization entity (BES entity 80) can perform either barriers, eureka, or both simultaneously. Additionally, interrupts can be generated at critical points.

Figure 10 shows the communication and state information required next to a PE 102 (in this embodiment, the communication and state
30 information is within node router 140) for one node of the system. BES unit 145 contains the state information and controller logic for the BES entities 80. One

embodiment allows multiple BES entities 80 within a system for multiprogramming purposes. In one embodiment, PE 102 communicates with BES unit 145 via memory-mapped loads and stores.

In one embodiment, BES unit 145 includes node state 142 having
 5 $D \times B \times 3$ bits, where D represents the number of BES domains 82, B represents the number of barriers in each BES domain 82, and the 3 bits encode the BES unit state as shown in the barrier/eureka synchronization states of Figure 18 for each domain and barrier. In one such embodiment, D is thirty-two (32), supporting thirty-two BES domains, and B is one, supporting one barrier in each
 10 BES domain 82. In another such embodiment, D is thirty-two (32), supporting thirty-two BES domains, and B is two, supporting two barriers in each BES domain 82.

In one embodiment, BES unit 145 also includes dynamic state 144 having $D \times B \times (5 + (2 \times N))$ bits, where D represents the number of BES
 15 domains 82, B represents the number of barriers in each BES domain 82, N represents the number of dimensions in the network (e.g., a k-ary n-cube network), and the bits encode which children have joined the BES barrier from the FANIN tree, and which children have been sent the BES barrier-completion signal on the FANOUT tree.

20 In one embodiment, BES unit 145 includes connection state 146 having $D \times (1 + (N \times 2) + \log_2((N \times 2) + 2))$ bits, where D represents the number of BES domains 82, N represents the number of dimensions in the network, and the bits encode the location of the link connections to the BES unit's parent and children.

25 A memory-mapped load operation returns the current state of BES unit 145 to PE 102 running in processor 202. A memory-mapped store operation forwards "operations" (commands) from processor 202 to BES unit 145. BES unit 145 also communicates to processor 202 via an interrupt mechanism which is triggered upon receipt of a eureka or barrier-completion
 30 signal. Figure 10 also depicts how one embodiment of BES unit 145 communicates with the FANIN/FANOUT trees.

Figure 18 describes the user-visible states of one embodiment of an individual BES unit 80. Figure 19 describes the user-visible operations which are implemented in one embodiment of PE 102 to change the BES entity state and cause the synchronization operation to be performed.

5 Figure 20 (a table which is comprised of Figures 20A and 20B side-by-side) shows the BES entity states and operations that, in one embodiment, are used by the user to implement a barrier (in this embodiment, some other states exist in the tree to implement the message passing used to provide the user-visible states and operations; see e.g., Figures 14 and 15 which
10 show internal states not visible to the user). In one embodiment, this state information is stored in the C-chip shown in Figure 11. A simple barrier is an S_BAR → S_ARM → S_BAR transition. The S_BAR → S_ARM transition occurs as PE 102 executes an OP_BAR operation. This is the indication from PE 102 to barrier control means to cause the PE 102 to join the barrier. The
15 S_ARM → S_BAR transition occurs as all PEs 102 join and the barrier propagates down the FANIN tree and up the FANOUT tree. The S_IDLE state can also be used as a third state for the simple barrier (via OP_CLEAR). This can be particularly useful with barrier interrupts to indicate that the barrier has been "seen". In all other aspects, S_BAR and S_IDLE are equivalent.

20 Figure 16 shows the three-state transition, as seen by a user in one embodiment, for a simple, reusable eureka (other transitions, as shown in Figures 14 and 15, implement the message passing used to provide the user-visible transitions). The barrier synchronization that is inherent in or folded into the eureka operation makes the eureka immediately reusable. Each PE 102 starts in
25 the S_BAR (S_IDLE) state. One (or more) of the processors execute OP_EUR_B. This sends the eureka, changing the other states to S_EUR. As each processor "sees" the eureka, that processor joins the subsequent barrier (to indicate that it has "seen" the eureka). This leaves the state for all processors in S_ARM momentarily until the barrier completes, which then moves the state to
30 S_BAR.

The processors can receive interrupts from the BESU. The OP_INT operation enables interrupt upon receipt of a eureka event. The OP_BAR_I operation both arms the barrier and enables an interrupt on completion. The S_EUR_I is equivalent to the S_EUR state except that it indicates that an interrupt was sent. The S_BAR_I is equivalent to the S_BAR state except that it indicates that an interrupt was sent.

Table 1, below, shows the operations that are sent down the FANIN tree. Note that FI_EB indicates that the eureka occurred first, followed by the barrier.

10

Table 1: FANIN operations	
FI_E	Issue Eureka
FI_B	Issue Barrier
FI_EB	Issue Eureka, Issue Barrier

15

Table 2, below, shows the FANOUT tree operations. Note that FO_BE indicates that the barrier completed first, followed by a subsequent eureka event.

20

Table 2: FANOUT operations	
FO_E	Eureka Received
FO_B	Barrier Completed
FO_BE	Barrier completed, Eureka Received

Table 3, below, shows one embodiment of the BES entity state information stored in each node router 140.

Table 3: BES entity state in router	
BMCS	bit mask describing which children from the FANIN tree have requested to join the barrier
5 FANIN state (FI_S)	FI_S_IDLE: Idle FI_S_EUREKA: Eureka has arrived FI_S_BARRIER: All children have joined the barrier FI_S_EUREKA_BARRIER: Eureka has arrived and all children have subsequently joined the barrier
FANOUT state (FO_S)	FO_S_IDLE: Idle FO_S_EUREKA: Eureka received FO_S_BARRIER: Barrier completed FO_S_BARRIER_EUREKA: Barrier completed and a later eureka received

In one embodiment, BMCS is 7 bits, indicating which children have joined a barrier; FI_S is two bits encoding the above states; and FO_S is
 10 two bits indicating the above states.

Figures 20A and 20B are to be next to one another to form a single table which shows the leaf (or user-visible) BESU state changes and actions resulting from the various operations it receives from the PE 102 and from the FANOUT tree. FO_E causes a "Eureka Event." FO_B causes "Barrier
 15 Completion." FO_BE is the same as FO_B followed by FO_E.

Figure 11 shows one exemplary embodiment of a node router 140 which can be used in interface-and-network router 206 of the present invention, capable of implementing a 3-D (three-dimensional) torus network for a plurality of PEs 102. Examples for this type of 3-D node router 140 are shown and
5 described in this application, though the present invention is not limited to this style of router, and other embodiments have generalized K-ary N-cube routers or Omega routers. Node router 140 has seven physical input channels and seven physical output channels, which feed the one attached PE 102 connection and the plus X, Y, and Z and minus X, Y, and Z connections to this node (for a total of
10 seven connections). BES messages travel over these seven physical channels to implement the FANIN and FANOUT trees on the 3-D torus fabric. Figure 11 also shows that in this embodiment, node router 140 contains state information needed to implement FANIN and FANOUT trees. Node state 142 contains node state information. In one embodiment, one-hundred ninety-two (192) bits of
15 node state 142 information are kept, (i.e., 32 times 2 times 3 for the thirty-two BES domains 82, two barriers per BES domain 82, and the 3 bits encode the BES unit state as shown in Figure 18 for each domain and barrier). In this embodiment, BES unit 145 also includes dynamic state 144 having
 $D \times B \times (5 + (2 \times N))$ bits, where D is thirty-two and represents the number of BES
20 domains 82, B is two and represents the number of barriers in each BES domain 82, N is three and represents the number of dimensions in the network (e.g., a k-ary n-cube), and these $2 \times N$ bits encode which children have joined the BES barrier from the FANIN tree, and which children have been sent the BES barrier-completion signal on the FANOUT tree. In this embodiment, 32 domains \times 10
25 bits per domain are used to encode connection state 146.

The FANIN tree need not be exactly the same as the FANOUT tree. In one embodiment, the root 70 of the FANIN tree and the root 70 of the FANOUT tree are preferably physically adjacent, and both trees must have the same BES units as leaves 74. For the sake of simplicity of explanation, the
30 examples shown here assume that the FANIN and FANOUT trees of BES entity 80 are identical.

In one embodiment, a distinct BES entity 80 is implemented for each BES domain 82. Each BES domain 82 has a domain identifier. Each BES domain 82 may represent multiple BES entities 80. The BES entities 80 are built and defined via the domain state information contained in every node router 140.

5 Direct connections between nodes in the FANIN and FANOUT trees typically correspond to direct physical connections between node router 140, and the node router 140 themselves correspond to the nodes of the FANIN and FANOUT trees. Non-overlapping BES entities 80 may use the same domain identifier. ("Non-overlapping BES entities 80" are defined as two or more BES entities 80

10 whose FANIN and FANOUT trees reside in different and separate sets of node router 140 in the system.) This allows the system 100 to require relatively fewer domain identifiers, yet support many BES entities 80.

Figure 12 shows one embodiment of the BES domain state information held in each node router 140 that describes the BES entity 80 (the

15 FANIN and FANOUT trees) which uses that node router 140. This state information defines the barrier/eureka synchronization tree by describing its connections. In one embodiment, this state information is stored in the R-chip shown in Figure 11. BMCCI 720 is used to detect when all children have joined the FANIN of FI_B. In one embodiment, BMCCI 720 comprises a bit mask

20 with one bit for each possible input channel to that node router 140. In an alternative embodiment, BMCCI 720 comprises a count of the input channels. BMCO 721 is a bit mask with one bit per output channel to specify the children for the FANOUT tree. It is used to specify distribution of the messages towards the leaves of the FANOUT tree. Fanout messages are sent to each of the

25 corresponding output channels where a BMCO bit is "set" in BMCO 721. PTRCI 722 specifies which output channel is the parent for the FANIN tree. FANIN messages are sent to the output channel specified by the value in PTRCI. Special values for PTRCI are used to indicate when the node is the root of the FANIN tree. (When at the root of the FANIN tree, a FANOUT message is sent

30 to the FANOUT tree.) In one embodiment, the BMCCI 720 and the BMCO 721 are implemented sharing the same bit-mask (i.e., they are the same register), and

thus the FANIN and FANOUT trees traverse the identical set of node routers 140. For the example node router 140, the bit-mask is 7 bits wide. In one embodiment, PTRCO 723 specifies which input channel is the parent for the FANOUT tree. In one embodiment, PTRCO and PTRCI are the same (i.e., they are one register), and thus the FANIN and FANOUT trees traverse the identical set of node routers 140.

Figure 22 and the tables in Figures 23 and 24 show an example configuration for BES entity 80. Figure 22 shows a conceptual diagram of the connections of a portion of a three-dimensional torus network of physical nodes 200 showing the cartesian coordinates of each physical node 200 as a six-digit number (the first digit of which represent the Z position, the middle digit of which represent the y position, and the last digit of which represent the x position). Note that it is assumed that the FANIN and FANOUT trees are identical for this example; BMCCI 720 and BMCO 721 are represented by a single 7-bit mask register. The table in Figure 24 shows a particular encoding for one embodiment of the PTRCI ("Barrier Parent Node"). Figure 22 shows the tree that is created. (The numbers next to each node identify the node. Node (1,1,1) is the root 70.) The table in Figure 23 shows the PTRCI values corresponding to each node ("PARENT FIELD"). It also shows the merged BMCCI-BMCO mask ("CHILD MASK"). The right-most bit corresponds to the processor channels (the barrier connection to the local processor 202 in Figure 11). The other six bits correspond to the +X, -X, +Y, -Y, +Z, and -Z channels of Figure 11 (right to left). Note that in this example the nodes (2,0,0), (2,1,0), (2,2,0), (2,0,1), (2,1,1), and (2,2,1) are not leaves of the tree, as indicated by the low-order bit of their CHILD MASK being 0. They simply propagate barrier/eureka traffic between their adjacent nodes.

The state information held in the node router 140 for each BES entity 80 is shown in Table 3. (Again note: each FANIN/FANOUT BES domain can contain one or more BES entities 80.) The state information components are separated in order to provide the simplest representation. The BM/CS describes which (or in one embodiment, how many) children have joined the FANIN tree

barrier. The additional FANIN states includes the IDLE, EUREKA, BARRIER, and BARRIER_EUREKA. EUREKA and BARRIER have similar meaning to their fanin counterparts. BARRIER_EUREKA means that the barrier has fired and was followed by a subsequent EUREKA. (EUREKA_BARRIER does not
 5 exist during fanout since a fanout eureka that is followed by a subsequent fanout barrier results in the foregoing eureka being ignored.

The table in Figure 14 shows the transitions for the FANIN tree states and operations. The SEND column indicates the changes that occur at the time a message is sent to the next higher tree level. If the node is the root of the
 10 FANIN tree, a message is sent to the root of the FANOUT tree. For simplicity here, it is assumed that a SEND does not occur at the same time as the receipt of a fanin message. SEND cannot occur when the BES entity 80 is in the state FI_S_IDLE (since there is nothing to send). For any of the other states, the resultant state after the SEND is FI_S_IDLE. Figure 14 shows which message is
 15 sent on a SEND within each SEND table entry box. The first entry applies if the node is not the root and the second if it is. SEND's result is FI_E, FI_B, or FI_EB messages when not the root. When the node is the root, FO_E or FO_B results. FO_BE never happens at this point because FANOUT eureka's are ignored when FANOUT barriers catch up to them.

20 FI_E causes in a change to FI_S_EUREKA state as shown in Figure 14. FI_B causes the BM/CS to be updated (either setting a bit in a mask corresponding to the input channel, or else incrementing a counter). Once the barrier is complete, probably detected by an equality check between BM/CS and BM/CCI, the state changes to either FI_S_BAR (if in FI_S_IDLE before) or
 25 FI_S_EUREKA_BARRIER (if in FI_S_EUREKA before). FI_EB is identical to FI_E followed by FI_B. No FANIN messages should be received when in the FI_S_BARRIER or FI_S_EUREKA_BARRIER during normal operation.

The table in Figure 15 shows the transitions for the FANOUT states and operations. Again, the SEND column shows the messages that are
 30 propagated up the FANOUT tree for each non-IDLE fanout state. Whereas the fanin messages were single messages, the fanout messages are broadcast

(multicast). The state transitions in Figure 15 assume the broadcast is instantaneous (i.e. each fanout message is sent at the same time). The broadcast doesn't really have to be instantaneous if fanout messages are buffered at the output channel (the buffers are filled instantaneously, though). FO_E causes
5 FO_S_EUREKA when previously in FO_S_IDLE or FO_S_EUREKA states. If previously in the FO_S_BARRIER or FO_S_BARRIER_EUREKA the state goes to FO_S_BARRIER_EUREKA; this corresponds to a subsequent eureka catching up to a earlier barrier (probably because the barrier completion got held up by network contention). FO_B causes FO_S_BARRIER. If the state was
10 previously FO_S_EUREKA, the eureka is ignored because if it ever reached the leaves it would be ignored anyway (the leaves of the subtree rooted at this node must all either be in state S_ARM or S_ARM_I). FO_BE is equivalent to FO_B followed by FO_E.

Figure 13A and 13B show how the BES entity messages
15 (operations) integrate with the data traffic on a node router 140. Figure 13A shows that BES entity messages from an input physical channel 139 are directed to either the BES unit 145 (if it is a fanin or fanout message) or along the normal path to the normal data-communications controller 150 (if it is a normal message). Similarly, Figure 13B shows how the output physical channel 139 is
20 shared between either normal data messages or the barrier/eureka messages. The point is that barrier/eureka traffic (i.e., BES messages) and the normal data traffic (i.e., data messages) need share only the physical channel 139. The barrier/eureka traffic need not abide by the buffering or flow control restrictions of the data traffic since all the barrier/eureka state information required in the
25 network is encoded in the BES state within each node router 140 (see Table 3, above). Since the size of the state information is modest, it can affordably be held on the node router 140 in BES buffering, separate from the data traffic buffering. Also, since the buffering is separate, barrier messages can safely be prioritized differently from normal data traffic. In one embodiment for instance,
30 in order to reduce barrier and eureka latencies, the barrier/eureka messages have higher priority than data messages.

Barrier/Eureka Synchronization

The barrier/eureka synchronization mechanism visible to the user in the Barrier/Eureka Synchronization Architecture (BESA) of the present invention is completely redesigned from the version used in the Cray T3D model massively parallel processing system manufactured by Cray Research Inc., the assignee of the present invention. To start with, barrier states are not encoded as single bits. Instead, each barrier/eureka synchronization unit is controlled by a three-bit state code as indicated in the barrier-state encoding table in Figure 18.

10 The table in Figure 19 shows various operations available for a barrier/eureka synchronization unit.

A simple T3D barrier is a 0→1→0 transition sequence: a 0→1 transition which occurs as the local PE 102 "arms" the barrier, and a 1→0 transition which occurs as the barrier "completes". A simple BESA barrier is a S_BAR → S_ARM → S_BAR transition sequence: a S_BAR → S_ARM transition which occurs as the local PE 102 executes the OP_BAR operation on the synchronization unit, and the S_ARM → S_BAR transition which occurs as the barrier completes. Figure 17 indicates these transitions. The S_IDLE state can also be used as a third state for the simple barrier (using the OP_CLEAR

15 S_BAR → S_ARM → S_BAR transition sequence: a S_BAR → S_ARM transition which occurs as the local PE 102 executes the OP_BAR operation on the synchronization unit, and the S_ARM → S_BAR transition which occurs as the barrier completes. Figure 17 indicates these transitions. The S_IDLE state can also be used as a third state for the simple barrier (using the OP_CLEAR

20 operation). This can be useful to indicate that the barrier completion event has been seen (perhaps particularly when using barriers with interrupts). In all other aspects, the S_BAR and S_IDLE states are equivalent.

Referring to Figure 16, a simple re-usable BESA eureka event is a three-state transition. Unlike T3D eureka, BESA eureka do not require an additional barrier synchronization to re-use the BESA eureka, since the barrier is folded into the same synchronization unit as the eureka. In effect, a BESA eureka is a eureka event followed by a barrier completion (or, equivalently, a barrier completion followed by a eureka event). As each PE 102 sees the eureka event (indicated by the S_EUR state), it arms the barrier that will clear out the eureka (and which will indicate that all processors have seen the eureka) by

25 additional barrier synchronization to re-use the BESA eureka, since the barrier is folded into the same synchronization unit as the eureka. In effect, a BESA eureka is a eureka event followed by a barrier completion (or, equivalently, a barrier completion followed by a eureka event). As each PE 102 sees the eureka event (indicated by the S_EUR state), it arms the barrier that will clear out the eureka (and which will indicate that all processors have seen the eureka) by

30 executing the OP_BAR operation on the synchronization unit. The PE 102 that

signals the eureka can also go directly from the S_BAR state to the S_ARM state using the OP_EUR_B operation. Once the barrier completes, the eureka can be reused. Figure 16 shows these transitions. (As in the simple barrier transitions shown in Figure 17, the simple eureka transitions shown in Figure 16 could be
 5 augmented to include the S_IDLE state as a fourth state.)

The PE 102 can receive interrupts from either eureka event or from a barrier completion event (or both). The OP_INT operation enables an interrupt upon receipt of a eureka event. The OP_BAR_I operation both arms the barrier, and enables an interrupt on barrier completion. The S_EUR_I state is
 10 equivalent to the S_EUR state, except that it indicates that an interrupt was signalled. Similarly, the S_BAR_I state is equivalent to the S_BAR state, except that it indicates that an interrupt was signalled. The table in Figure 20 (comprised of Figures 20A and 20B side-by-side) shows all states and all transitions for the barrier/eureka synchronization units.

15 The OP_RESET operation is a reset feature to recover from system errors by placing the barrier/eureka synchronization unit in a known state. Note that this does not reset the entire tree, only the leaf. (See Section 12.3.)

An implementation of the present invention should specify a fixed
 20 maximum delay during which all barrier/eureka operations are guaranteed to complete. (This delay should only be a few microseconds.) A barrier/eureka state can be swapped out after delaying for this amount of time, given that there are no barrier/eureka operations issued to the given barrier/eureka synchronization unit during this delay. Also after this delay, a known
 25 barrier/eureka state (either S_BAR or S_BAR_I) can always be reached by issuing an OP_BAR at all the nodes within the partition that are not already in the S_ARM or S_ARM_I state, and waiting for the resultant barrier completion event. A previously-swapped-out barrier/eureka synchronization unit state can be swapped into a new barrier domain by a series of operations that cause the
 30 swapped state to be duplicated. (E.g., start all nodes in the S_IDLE state. Complete a barrier for these nodes requiring the S_BAR or S_BAR_I states.

After that, issue an OP_INT for those nodes requiring S_IDLE_I state, and the nodes requiring S_EUR or S_EUR_I states can issue an OP_EUR.

Concurrently, the nodes requiring the S_ARM or S_ARM_I states issue their OP_BAR or OP_BAR_I. Note that the system cannot simultaneously have one
5 or more swapped nodes in the S_IDLE, S_IDLE_I, S_BAR, or S_BAR_I states while one or more swapped nodes are also in the S_EUR or S_EUR_I states.)

There are no ordering constraints between different barrier/eureka synchronization units (even among the two units within the same domain). Eureka events and barrier completion events to different units may occur in any
10 order.

Barrier registers are accessed through non-cached memory space.

Figure 21 is an exemplary structure of a barrier register physical address 210 for one embodiment of the present invention. The bit marked "P" indicates privilege (wherein 0=user and 1=system). The bits marked "C C C C"
15 "C" specify context selection. The bit marked "B" selects between the first and second barrier register, and thus selects one of the two barrier synchronization units that are within each barrier domain. The bits marked "Q" are implementation-defined values (likely zero). The bits marked "z" are reserved (must be zero, else trap).

20 A read operation directed to the address shown in Figure 21 returns data having the state of the appropriate barrier/eureka synchronization unit in bits 0:2. A write operation involves the operation specified by bits 0:2 on the appropriate barrier/eureka synchronization unit. In one embodiment, all barrier operations are unprivileged, except for OP_RESET.

25 Virtual Barrier/Eureka Network

In one embodiment, in addition to carrying inter-processor data communication, a torus network acts as a vehicle for a plurality of virtual barrier/eureka synchronization networks (VBESNs). These VBESNs behave in a manner similar to the BES entities 80 described above, and are called "virtual"
30 because each runs on a separate virtual network, wherein a plurality of virtual networks can share a single physical network. The barrier network in BESA is

implemented as a virtual network using the same physical links as the communication torus. Combining the data and synchronization virtual networks onto a physical network allows more efficient use of the physical wires connecting the network.

5 In one such embodiment, the VBESNs have higher priority for the physical channel between nodes than other traffic, with some added restrictions in order to avoid bandwidth hogging by the VBESNs. Non-blocking data traffic is allowed to utilize the channels in a time-multiplexed manner with the VBESN traffic. A VBESN tree need not be configured symmetrically. A
10 given node in the tree collects fanin events until it determines it is appropriate to pass an event towards the root of the tree. Fanout events are passed towards the leaves as soon as they are detected.

 In this embodiment, each node has thirty-two barrier domains 82; and each barrier domain implements one barrier and can be configured
15 independently of the other thirty-one barrier domains 82. Each barrier domain 82 can be configured into any number of independent sub-networks, each having a BES entity 80, with the constraint that no two sub-networks of the same virtual network (i.e., within the same one-barrier group) is allowed to share a node 200. Valid configurations are built through nearest-neighbor connections only. A
20 given node 200 in a tree is able to fanin/fanout to its six nearest neighbors and to the PE 102 to which it is attached.

 Each VBESN uses the "CHILD MASK" of its BMCCI[i] register 720 to select its children (i.e., the children of a node are the inputs to be combined on fanin and the outputs to be used on fanout). The "PARENT
25 FIELD" of the PTRCI[i] 722 (using the same i index) is used to select the parent node for this node. In this embodiment, barriers/eurekas fanout on the same communications links, but proceeding in opposite directions, that they fanin (thus BMCO register 721 is the same as BMCCI register 720, and PTRCI register 722 is the same as PTRCO register 723). In one such embodiment, each
30 barrier domain has its own network configuration registers 720 and 722 on each given node as described above for Figures 22, 23, and 24.

There are two ways in which a given node 200 can join a VBESN barrier, as far as the network is concerned. The first is simply to join the barrier as described above in the discussion of BES entities 80. The other is to modify the appropriate BMCCI[i] register 720 and PTRCI[i] register 722 to remove that
5 particular node from the barrier tree (note that this must be done at the nearest fork, which is not necessarily on the retreating node.

It is to be understood that the above description is intended to be illustrative, and not restrictive. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the
10 invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

What is claimed is:

1. A computer system comprising:
a plurality of processor entities (PEs) including a first processor entity
(PE) and a second PE;
5 a memory coupled to the first PE;
a communications network, wherein the communications network
connects to each one of the plurality of PEs and passes messages having
commands and messages having data and barrier/eureka-synchronization (BES)
messages from one PE to another, wherein the BES messages include a
10 barrier-join message and a barrier-complete message, the communications
network including a path between the first PE and the second PE; and
a BES domain coupled to the communications network, the BES
domain comprising:
BES messaging means for sending and receiving BES
15 messages on the communications network between pairs of the
plurality of PEs including on the path between the first PE and the
second PE.
2. The computer system according to claim 1, wherein the BES messages
20 further include a eureka message.
3. The computer system according to claim 1, further comprising:
for each one of the plurality of PEs, a node router, wherein the first PE
includes a first node router, and the first node router is coupled to the respective
25 node routers associated with each of a first subset of the plurality of PEs.
4. The computer system according to claim 3, the BES domain further
comprising: for each one of the plurality of PEs, a BES-state register,
wherein the BES-state register for the first PE stores an
30 indication of one of a plurality of BES states.

5. The computer system according to claim 4, the first node router further comprising

a first plurality of node-interconnection ports for the first PE, wherein the first plurality of node-interconnection ports is operable to connect the first PE to the first subset of the plurality of PEs;

and the BES domain further comprising a first portion of the BES domain for the first PE, the first portion of the BES domain comprising:

a BES child connection register coupled to the first plurality of node interconnection ports, wherein the BES child connection register specifies which ones of the first subset of the plurality of PEs are children of the first node router; and

a BES parent connection register coupled to the first plurality of node interconnection ports, wherein the BES parent connection register specifies which one of the first subset of the plurality of PEs is a parent of the first PE.

6. A first node router for use in a multiprocessor computer system having a plurality of other node routers, the first node router comprising:

a first plurality of node interconnection ports, each operable to connect the first node router to a first subset of the plurality of other node routers;

a first barrier/eureka-synchronization (BES) messaging circuit coupled to the first plurality of node interconnection ports, wherein the first BES messaging circuit selectively sends and receives BES messages between the first node router and the first subset of the plurality of other node routers, wherein the BES messages include a barrier-join message and a barrier-complete message; and

a first BES state register coupled to the first BES messaging circuit;

a first BES state changer coupled to the first BES state register and to the first BES messaging circuit, and operable to change a BES state stored in the first BES state register in response to a previous BES state and to a BES message received by the first BES messaging circuit.

7. The first node router according to claim 6, further comprising:
a first BES child connection register coupled to the first BES
messaging circuit, wherein the first BES child connection register specifies
which ones of the plurality of other node routers are children of the first node
5 router; and
a first BES parent connection register coupled to the first BES
messaging circuit, wherein the first BES parent connection register specifies
which one of the plurality of other node routers is a parent of the first node
router.
- 10 8. A massively parallel processor system comprising:
a memory;
a plurality of processor entities (PEs) including a first PE and a first
subset of the plurality of PEs, the first PE coupled to the memory;
15 a virtual barrier/eureka synchronization network (VBESN) running on
a physical data-communication network, the physical data-communication
network coupling the plurality of PEs and sending a plurality of types of
messages between pairs of PEs, the VBESN comprising:
barrier/eureka-synchronization (BES) messaging means for
20 sending and receiving BES messages on the physical
data-communication network between the first PE and the first
subset of the plurality of PEs, wherein the BES messages
comprise a barrier-complete message;
a BES state storage means; and
25 BES state changing means for changing a BES state stored in
the BES state storage means and responsive to the BES state and
to a BES message received by the BES messaging means.
9. The system according to claim 8, wherein the BES messages further
30 comprise a barrier-join message.

10. The system according to claim 8, wherein the BES messages further
comprise a eureka message
11. The system according to claim 9, wherein the BES messages further
5 comprise a eureka message
12. The system according to claim 8, further comprising:
BES child-connection storage means for specifying which ones of the
first subset of the plurality of other PEs are children of the first PE; and
10 BES parent-connection register means for specifying which one of the
first subset of the plurality of other node routers is a parent of the first PE.
13. The system according to claim 9, further comprising:
BES child-connection storage means for specifying which ones of the
15 first subset of the plurality of other PEs are children of the first PE; and
BES parent-connection register means for specifying which one of the
first subset of the plurality of other node routers is a parent of the first PE.
14. The system according to claim 10, further comprising:
20 BES child-connection storage means for specifying which ones of the
first subset of the plurality of other PEs are children of the first PE; and
BES parent-connection register means for specifying which one of the
first subset of the plurality of other node routers is a parent of the first PE.
- 25 15. The system according to claim 8, wherein the BES state storage means
simultaneously stores a separate BES state for each one of a plurality of BES
domains.
16. A method for synchronizing barrier and eureka events in a computer
30 system having a physical data-communication network, the physical

data-communication network connected to a plurality of processor entities (PEs) including a first PE and a plurality of other PEs, comprising the steps of:

- receiving barrier/eureka-synchronization (BES) messages on the physical data-communication network to the first PE from a first subset of the plurality of other PEs;
- 5 sending BES messages on the physical data-communication network from the first PE to a second subset of the plurality of other PEs;
- storing a BES state for the first PE; and
- changing the BES state responsive to the BES state and to a received
- 10 BES message,
- and wherein the BES messages comprise a barrier-join message.

17. The method according to claim 16, wherein the BES messages further comprise a eureka message

15

18. The method according to claim 16, wherein the BES messages further comprise a barrier-complete message

19. The method according to claim 16, further comprising the steps of:
- 20 keeping a children value indicative of the first subset of the plurality of other PEs which are children of the first PE; and
- keeping a parent value indicative of the second subset of the plurality of other PEs which is a parent of the first PE,
- and wherein:

- 25 the step of receiving BES messages depends on the children value,
- and
- the step of sending BES messages depends on the parent value.




FIG. 1

2/25




FIG. 2

3/25




FIG. 3

4 / 25




FIG. 4

5/25




FIG. 5

6/25




FIG. 6

7/25





FIG. 7

8/25



9/25




FIG. 9

10/25




FIG. 10




FIG. 11

12/25




FIG. 12

13/25




FIG. 13A




FIG. 13B

CURRENT FANIN STATE	OPERATION RECEIVED			
	SEND	FI_E	FI_B	FI_EB
FI_S_IDLE	N/A	GOTO FI_S_EUREKA	UPDATE BM/CS; IF (BAR COMPLETE) GOTO FI_S_BARRIER ELSE GOTO FI_S_IDLE	UPDATE BM/CS; IF (BAR COMPLETE) GOTO FI_S_EUR_BAR ELSE GOTO FI_S_EUREKA
FI_S_EUREKA	GOTO FI_S_IDLE (FI_E, FO_E)	GOTO FI_S_EUREKA	UPDATE BM/CS; IF (BAR COMPLETE) GOTO FI_S_EUR_BAR ELSE GOTO FI_S_EUREKA	UPDATE BM/CS; IF (BAR COMPLETE) GOTO FI_S_EUR_BAR ELSE GOTO FI_S_EUREKA
FI_S_BARRIER	GOTO FI_S_IDLE (FI_B, FO_B)	UNDEFINED	UNDEFINED	UNDEFINED
FI_S_EUR_BAR	GOTO FI_S_IDLE FI_EB, FO_B)*	UNDEFINED	UNDEFINED	UNDEFINED

* IGNORE PRIOR EUREKA IN THIS CASE

FIG. 14

15/25

CURRENT FANOUT STATE	OPERATION RECEIVED			
	SEND	FO_E	FO_B	FO_BE
FO_S_IDLE	N/A	GOTO FO_S_EUREKA	GOTO FO_S_BARRIER	GOTO FO_S_BARRIER_ EUREKA
FO_S_EUREKA	GOTO FO_S_IDLE (FO_E)	GOTO FO_S_EUREKA	GOTO FO_S_BARRIER*	GOTO FO_S_BARRIER_ EUREKA*
FO_S_BARRIER	GOTO FO_S_IDLE (FO_B)	GOTO FO_S_BARRIER_ EUREKA	UNDEFINED	UNDEFINED
FO_S_BARRIER_EUREKA	GOTO FI_S_IDLE (FO_BE)	GOTO FO_S_BARRIER_ EUREKA	UNDEFINED	UNDEFINED

* IGNORE PRIOR EUREKA IN THIS CASE

FIG. 15

16/25




FIG. 16

17/25




FIG. 17

VALUE	NAME	DESCRIPTION
000	S_IDLE	IDLE
001	S_IDLE_I	AN INTERRUPT WILL OCCUR WHEN A EUREKA EVENT COMES
010	S_EUR	A EUREKA EVENT CAME
011	S_EUR_I	A EUREKA CAME, INTERRUPT SIGNALLED
100	S_ARM	BARRIER IS ARMED
101	S_ARM_I	BARRIER IS ARMED, AN INTERRUPT WILL OCCUR ON COMPLETION
110	S_BAR	BARRIER JUST COMPLETED
111	S_BAR_I	BARRIER JUST COMPLETED, INTERRUPT SIGNALLED

FIG. 18

VALUE	NAME	DESCRIPTION
000	OP_CLEAR	CLEAR
001		RESERVED
010	OP_EUR	SEND EUREKA
011	OP_INT	PLEASE INTERRUPT WHEN A EUREKA EVENT OCCURS
100	OP_BAR	ARM BARRIER
101	OP_BAR_I	ARM BARRIER, PLEASE INTERRUPT ON COMPLETION
110	OP_EUR_B	SEND EUREKA, ARM BARRIER
111	OP_RESET	RESET (SYSTEM PRIVILEGED)

FIG. 19

FIG. 20A
FIG. 20B

FIG. 20

STATES STORED IN C-CHIP	OPERATIONS FROM PE							OP. FROM FANOUT TREE	
	OP_CLEAR	OP_INT	OP_EUR	OP_BAR	OP_BAR_I	OP_EUR_B	OP_RESET	EUREKA EVENT	BARRIER COMPLETION
S_IDLE	NOP	GOTO S_IDLE_I	SEND EUREKA, GOTO S_EUR	ARM BARRIER, GOTO S_ARM	ARM BARRIER, GOTO S_ARM-I	SEND EUREKA, ARM BARRIER, GOTO S_ARM	GOTO S_IDLE	GOTO S_EUR	NOP
S_IDLE_I	GOTO S_IDLE	NOP	INTERRUPT, SEND EUREKA, GOTO S_EUR_I	ARM BARRIER, GOTO S_ARM	ARM BARRIER, GOTO S_ARM_I	INTERRUPT, SEND EUREKA, ARM BARRIER, GOTO S_ARM	GOTO S_IDLE	INTERRUPT, GOTO S_EUR_I	NOP
S_EUR	NOP	INTERRUPT, GOTO S_EUR_I	NOP	ARM BARRIER, GOTO S_ARM	ARM BARRIER, GOTO S_ARM_I	ARM BARRIER, GOTO S_ARM	GOTO S_IDLE	NOP	NOP
S_EUR_I	GOTO S_EUR	NOP	NOP	ARM BARRIER, GOTO S_ARM	ARM BARRIER, GOTO S_ARM_I	ARM BARRIER, GOTO S_ARM	GOTO S_IDLE	NOP	NOP

FIG. 20A

21/25

S_ARM	NOP	NOP	NOP	NOP	NOP	NOP	NOP	GOTO S_IDLE	GOTO S_BAR_I
S_ARM_I	GOTO S_ARM	GOTO	NOP	NOP	NOP	NOP	NOP	GOTO S_IDLE	INTERUPT, GOTO S_BAR_I
S_BAR	GOTO S_IDLE	GOTO S_IDLE_I	SEND EUREKA, GOTO S_EUR	ARM BARRIER, GOTO S_ARM	ARM BARRIER, GOTO S_ARM_I	SEND EUREKA, ARM BARRIER, GOTO S_ARM	GOTO S_IDLE	GOTO S_EUR	NOP
S_BAR_I	GOTO S_IDLE	GOTO S_IDLE_I	SEND EUREKA, GOTO S_EUR	ARM BARRIER, GOTO S_ARM	ARM BARRIER, GOTO S_ARM_I	SEND EUREKA, ARM BARRIER, GOTO S_ARM	GOTO S_IDLE	GOTO S_EUR	NOP

FIG. 20B




FIG. 22

24/25

NODE (Z,Y,X)	PARENT FIELD	CHILD MASK	NODE (Z,Y,X)	PARENT FIELD	CHILD MASK	NODE (Z,Y,X)	PARENT FIELD	CHILD MASK	NODE (Z,Y,X)	PARENT FIELD	CHILD MASK
0,0,0	3	0000001	1,0,0	2	1100001	2,0,0	-3	0100000	3,0,0	-3	0000001
0,0,1	3	0000001	1,0,1	2	1100001	2,0,1	-3	0100000	3,0,1	-3	0000001
0,0,2	3	0000001	1,0,2	2	1100001				3,0,2	-3	0000001
0,1,0	3	0000001	1,1,0	1	1111001	2,1,0	-3	0100000	3,1,0	-3	0000001
0,1,1	3	0000001	1,1,1	0	1111111	2,1,1	-3	0100000	3,1,1	-3	0000001
0,1,2	3	0000001	1,1,2	-1	1111001				3,1,2	-3	0000001
0,2,0	3	0000001	1,2,0	-2	1100001	2,2,0	-3	0100000	3,2,0	-3	0000001
0,2,1	3	0000001	1,2,1	-2	1100001	2,2,1	-3	0100000	3,2,1	-3	0000001
0,2,2	3	0000001	1,2,2	-2	1100001				3,2,2	-3	0000001

FIG. 23

25/25

PARENT NODE	ENCODING
-Z	-3
-Y	-2
-X	-1
NONE (I.E., THIS IS THE ROOT NODE)	0
+X	+1
+Y	+2
-Z	+3

FIG. 24

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 96/07843

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G06F9/46

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>SYSTEMS & COMPUTERS IN JAPAN, vol. 24, no. 7, 1 January 1993, pages 69-76, XP000433487 ISHIHATA H ET AL: "ARCHITECTURE OF HIGHLY PARALLEL AP1000 COMPUTER" see page 70, left-hand column, line 11 - line 20 see page 70, right-hand column, line 14 - line 21 see page 70, right-hand column, line 34 - page 71, left-hand column, line 30 see page 74, right-hand column, line 12 - page 75, left-hand column, line 24</p> <p>--- -/--</p>	1-19

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

23 October 1996

Date of mailing of the international search report

06.11.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Brandt, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 96/07843

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JOURNAL OF PARALLEL AND DISTRIBUTED COMPUTING, vol. 25, no. 2, 1 March 1995, pages 126-132, XP000492656 O'KEEFE M T ET AL: "STATIC BARRIER MIMD: ARCHITECTURE AND PERFORMANCE ANALYSIS" see page 126, left-hand column, line 1 - right-hand column, line 6 see page 126, right-hand column, line 29 - page 128, left-hand column, line 4 ---	1-19
A	EP,A,0 473 452 (NCR CO) 4 March 1992 see column 1, line 5 - line 54 see column 2, line 16 - column 3, line 40 ---	1-19
P,A	WO,A,95 16236 (CRAY RESEARCH INC) 15 June 1995 see the whole document -----	1-19

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 96/07843

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0473452	04-03-92	JP-A- 4350758	04-12-92
-----	-----	-----	-----
WO-A-9516236	15-06-95	US-A- 5434995	18-07-95
		EP-A- 0733234	25-09-96
-----	-----	-----	-----